

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently amended) A method of imparting gloss to~~polishing~~ a hard surface, comprising:
applying a composition to the hard surface,
the composition comprising~~[[:]]~~ at least one glycol, and being substantially free of defoaming alcohol; and
leaving glycol on the hard surface to impart gloss.
2. (Original) The method according to claim 1, wherein the glycol is represented by Formula I:
$$\text{HO(R-CHCH}_2\text{O)}_n\text{H}$$
where R is an alkyl group containing 1 to 3 carbon atoms and n is 1 to 10,000.
3. (Original) The method according to claim 2, wherein n is 1 to 1,000.
4. (Original) The method according to claim 2, wherein n is 1 to 100.
5. (Original) The method according to claim 2, wherein n is 1 to 10.
6. (Original) The method according to claim 1, wherein the glycol is at least one of propylene glycol, dipropylene glycol, and polypropylene glycol.
7. (Original) The method according to claim 1, wherein the composition further comprises a wetting agent.
8. (Original) The method according to claim 1, further comprising diluting a concentrate to form the composition.

9. (Original) The method according to claim 1, wherein the composition comprises about 30 to about 70 wt-% glycol.

10. (Original) The method according to claim 1, wherein the composition comprises about 0.1 to about 70 wt-% glycol.

11. (Original) The method according to claim 1, wherein the composition comprises about 45 to about 55 wt-% glycol.

12. (Original) The method according to claim 11, wherein the glycol is represented by Formula I:



where R is an alkyl group containing 1 to 3 carbon atoms and n is 1 to 10,000.

13. (Original) The method according to claim 12, wherein the glycol is at least one of propylene glycol, dipropylene glycol, and polypropylene glycol.

14. (Original) The method according to claim 8, further comprising removing soil from the hard surface.

15. (Original) The method according to claim 14, further comprising rinsing the hard surface.

16. (Original) The method according to claim 1, wherein the hard surface is metal.

17. (Original) The method according to claim 1, wherein the hard surface is a tire.

18. (Original) A method of polishing a hard surface, comprising applying a composition to the hard surface, the composition comprising about 45 wt-% to about 55 wt-% propylene glycol.

19. (Original) The method according to claim 18, further comprising removing soil from the hard surface.

20. (Withdrawn) A method of polishing a hard surface, comprising applying a composition to the hard surface, the composition comprising an ethoxylate propoxylate.

21. (Withdrawn) The method according to claim 20, wherein applying comprises foaming the composition onto the hard surface from an unpressurized container.

22. (Withdrawn) An article of manufacture comprising:
a container of a composition including an alkoxyate and
instructions on how to use the composition as a polish.

23. (Withdrawn) An article of manufacture according to claim 22, further comprising a wet wipe saturated with the composition.

24. (Withdrawn) An article of manufacture according to claim 22, wherein the composition comprises glycol.

25. (Withdrawn) A method of polishing a hard surface, comprising applying a composition to the hard surface as a foam from an unpressurized container.